


R-6 SWING GATE OPERATOR



RESIDENTIAL

CLASS I VEHICULAR SWING GATE OPERATOR

www.PerformanceGateOpeners.com | (888) 378 - 1067 | Sales@PerformanceGateOpeners.com



COMPATIBLE WITH VIKING WIRELESS PRODUCTS

- Plug & Play connection for the Viking wireless expansion products.
- Viking Konnect - Wireless Kit provides secure and reliable wireless communication when the application requires two single ECUs.
- Viking Monitor - Remote access to the control board settings, operator diagnostics, controls, gate status and error notifications, all from the convenience of a computer or any compatible hand held device

BATTERY BACKUP INCLUDED

- Standard Battery Backup provides 400 continuous cycles at 100% duty cycle.
- With Viking's "True" Battery Backup System, batteries are not used during normal operations, maximizing battery life.

LIGHTNING PROTECTION

- Advanced lightning strike protection up to 20,000 volts / 10,000 amps
- On-board surge protection monitoring.

PROTECTION

- Multi-Layer Corrosion Protection
- G90 Galvanized
- Clear Zinc Plating
- UV Rated Powder Coating
- 1/4" Steel Chassis

INTEGRATED HEATER

- Built-in heater for operating temperatures down to -20° F.
- This will allow you run your operator in the coldest conditions.

SOLAR SMART

- Power Saving technology minimizes current draw while at standby.

DIAGNOSTICS DISPLAY

- On-board LCD screen displays voltages, amps, gate status and diagnostics.

Operational Voltage	24 VDC
Main Power Source Options	120/240 VAC Single Phase
Battery	12 VDC x 2
Battery Backup	400 Full Contin. Cycles (600 lbs)

Operating Speed	13-16 seconds per 90°
Operating Temperature	-20° F up to +160° F
Max Gate Capacity	700 lbs/ 14'
Max Duty Cycle	100% Contin. Cycle